



AC Dry Hydraulic Elevator Pump Motors 80 Starts per Hour

Squirrel Cage Induction, Dripproof, Ball Bearing, Class F Insulation
40°C Ambient, 3Ø, 60 Hz, WYE Start, Delta Run

| HP | Full Load RPM | Frame | Voltage | Amps (A) | | | | | Elevator Duty BTU Per Hour |
|-----|---------------|-------|---------|------------|-----------|--------------|----------|--------------|----------------------------|
| | | | | Delta | | | | WYE | |
| | | | | Full Load | No Load | Locked Rotor | KVA Code | Locked Rotor | |
| 15 | 1740 | 215T | 200 | 46 | 23 | 270 | G | 89 | 1859 |
| | 1735 | 215T | 230/460 | 39.2/19.6 | 19/9.5 | 230/115 | G | 76/38 | 1859 |
| | 1735 | 215T | 575 | 15.7 | 7.6 | 92 | G | 31 | 1859 |
| 20 | 1750 | 254T | 200 | 62 | 31 | 340 | G | 112 | 2263 |
| | 1750 | 254T | 230/460 | 54/27 | 27/13.5 | 296/148 | G | 98/49 | 2263 |
| | 1750 | 254T | 575 | 22 | 11 | 120 | G | 40 | 2263 |
| 25 | 1755 | 256T | 200 | 73 | 31 | 420 | G | 139 | 2360 |
| | 1755 | 256T | 230/460 | 62/31 | 26.4/13.2 | 366/183 | G | 120/60 | 2360 |
| | 1755 | 256T | 575 | 25 | 10.6 | 146 | G | 48 | 2360 |
| 30 | 1760 | 284T | 200 | 87 | 36 | 500 | G | 165 | 2774 |
| | 1760 | 284T | 230/460 | 74/37 | 31/15.5 | 430/215 | G | 142/71 | 2774 |
| | 1760 | 284T | 575 | 30 | 12.4 | 172 | G | 57 | 2774 |
| 40 | 1760 | 286T | 200 | 112 | 42 | 670 | G | 221 | 3282 |
| | 1760 | 286T | 230/460 | 98/49 | 37/18.5 | 580/290 | G | 192/96 | 3282 |
| | 1760 | 286T | 575 | 39 | 14.5 | 230 | G | 76 | 3282 |
| 50 | 1760 | 324T | 200 | 138 | 70 | 850 | G | 281 | 3869 |
| | 1760 | 324T | 230/460 | 118.8/59.4 | 62/31 | 740/370 | G | 244/122 | 3869 |
| | 1760 | 324T | 575 | 49 | 25 | 310 | G | 102 | 3869 |
| 60 | 1760 | 326T | 200 | 162 | 70 | 1000 | G | 330 | 4477 |
| | 1760 | 326T | 230/460 | 143.2/71.6 | 64/32 | 920/460 | G | 304/152 | 4477 |
| | 1760 | 326T | 575 | 58 | 26 | 370 | G | 122 | 4477 |
| 75 | 1770 | 364T | 200 | 210 | 87 | 1320 | G | 436 | 5253 |
| | 1770 | 364T | 230/460 | 180/90 | 72/36 | 1120/560 | G | 370/185 | 5253 |
| | 1770 | 364T | 575 | 72 | 29 | 450 | G | 149 | 5253 |
| 100 | 1780 | 365T | 230/460 | 228/114 | 76/38 | 1590/795 | G | 524/262 | 6015 |
| | 1780 | 365T | 575 | 91 | 30 | 636 | G | 210 | 6015 |

Imperial Electric
1503 Exeter Road
Akron, OH 44306
Phone: (330) 734-3600
Fax: (330) 734-3601
www.nidec-ise.com

Contact: Dennis Rhodes
Senior Sales Engineer
dennis.rhodes@nidec-ise.com
Ext. 3683

4/19/2017 REV B



AC Dry Hydraulic Elevator Pump Motors 120 Starts per Hour

Squirrel Cage Induction, Dripproof, Ball Bearing, Class F Insulation
40°C Ambient, 3Ø, 60 Hz, WYE Start, Delta Run

| HP | Full Load RPM | Frame | Voltage | Amps (A) | | | | | Elevator Duty BTU Per Hour |
|----|---------------|-------|---------|------------|-----------|--------------|----------|--------------|----------------------------|
| | | | | Delta | | | | WYE | |
| | | | | Full Load | No Load | Locked Rotor | KVA Code | Locked Rotor | |
| 10 | 1760 | 215T | 200 | 35.1 | 23 | 270 | K | 89 | 1295 |
| | 1760 | 215T | 230/460 | 28.4/14.4 | 19/9.5 | 230/115 | K | 76/38 | 1295 |
| | 1760 | 215T | 575 | 11.5 | 7.6 | 92 | K | 31 | 1295 |
| 15 | 1765 | 254T | 200 | 50 | 31 | 340 | J | 112 | 1675 |
| | 1765 | 254T | 230/460 | 43.3/21.7 | 27/13.5 | 296/148 | J | 98/49 | 1675 |
| | 1765 | 254T | 575 | 17.7 | 11 | 120 | J | 40 | 1675 |
| 20 | 1765 | 256T | 200 | 60.3 | 31 | 420 | J | 139 | 1868 |
| | 1765 | 256T | 230/460 | 52/26 | 26.4/13.2 | 366/183 | J | 120/60 | 1868 |
| | 1765 | 256T | 575 | 20.7 | 10.6 | 146 | J | 48 | 1868 |
| 25 | 1765 | 284T | 200 | 75 | 36 | 500 | H | 165 | 2312 |
| | 1765 | 284T | 230/460 | 64/32 | 31/15.5 | 430/215 | H | 142/71 | 2312 |
| | 1765 | 284T | 575 | 25.9 | 12.4 | 172 | H | 57 | 2312 |
| 30 | 1770 | 286T | 200 | 87.1 | 42 | 670 | J | 221 | 2517 |
| | 1770 | 286T | 230/460 | 76/38 | 37/18.5 | 580/290 | J | 192/96 | 2517 |
| | 1770 | 286T | 575 | 30.1 | 14.5 | 230 | J | 76 | 2517 |
| 40 | 1765 | 324T | 200 | 115 | 70 | 850 | J | 281 | 3132 |
| | 1765 | 324T | 230/460 | 100.6/50.3 | 62/31 | 740/370 | J | 244/122 | 3132 |
| | 1765 | 324T | 575 | 41 | 25 | 310 | J | 102 | 3132 |
| 50 | 1770 | 326T | 200 | 137 | 70 | 1000 | J | 330 | 3777 |
| | 1770 | 326T | 230/460 | 122.2/61.1 | 64/32 | 920/460 | J | 304/152 | 3777 |
| | 1770 | 326T | 575 | 50 | 26 | 370 | J | 122 | 3777 |
| 60 | 1775 | 364T | 200 | 168 | 87 | 1320 | J | 436 | 4257 |
| | 1775 | 364T | 230/460 | 150/75 | 72/36 | 1120/560 | J | 370/185 | 4257 |
| | 1775 | 364T | 575 | 60 | 29 | 450 | J | 149 | 4257 |
| 75 | 1780 | 365T | 230/460 | 178/89 | 76/38 | 1590/795 | K | 524/262 | 4511 |
| | 1780 | 365T | 575 | 71 | 30 | 636 | K | 210 | 4511 |

Imperial Electric
1503 Exeter Road
Akron, OH 44306
Phone: (330) 734-3600
Fax: (330) 734-3601
www.nidec-ise.com

Contact: Dennis Rhodes
Senior Sales Engineer
dennis.rhodes@nidec-ise.com
Ext. 3683

4/19/2017 REV B